

NOBILI



GEO ANTIS

3000

Turboatomizzatori trainati - 3000 litri

Trailed sprayers - 3000 liters



GEO-ANTIS 3000

Turboatomizzatore trainato per colture arboree, vigneti e frutteti

Trailed sprayer for arboriculture, vineyards and orchards

NOBILI presenta la risposta alle esigenze dell'azienda professionale che vuole ottimizzare tempi e risorse. La nuova cisterna 3000 litri in polietilene, si presenta con una gamma completa di gruppi ventola, accessori e dotazioni di serie che permettono di adattarlo a tutte le condizioni di utilizzo. Esempi ne sono l'ergonomico premixer e la possibilità di installare sensori di vegetazione per l'apertura/chiusura automatica dei getti. Design ribassato e compatto risulta ottimale anche nelle coltivazioni più vigorose. Il robusto doppio telaio zincato a caldo in acciaio ad alta resistenza assicura una macchina duratura nel tempo e resistenza alle aggressioni chimiche delle parti in ferro. Ruote a bassa pressione riducono il compattamento del suolo e il timone sterzante garantisce maneggevolezza. Abbinato ai gruppi ventola HF o ANTIS ad aspirazione anteriore permettono una copertura ottimale anche nelle piante ad alto fusto e al contempo una ridotta richiesta di potenza. Il carter frontale e la protezione inferiore mantengono al sicuro i dispositivi di controllo dell'irrorazione. Il controllo dell'irrorazione è affidato a sistemi elettrici, dalla semplice regolazione elettrica della pressione fino alle moderne soluzioni ISOBUS compatibili. Infine, NOBILI IOT BOX rende l'irroratrice conforme alle agevolazioni Agricoltura 4.0.

NOBILI presents the answer to the needs of the professional farm that wants to optimize time and resources. A new 3000 litres polyethylene tank is offered with a complete range of accessories and standard equipment adapting the sprayer to all conditions of use. Such as the ergonomic premixer and the possibility to equip the sprayer with vegetation sensors for the automatic opening / closing of the nozzles. Low and compact design ideal also in the most vigorous crops. The robust hot-galvanized double-structure frame, made of high-resistance steel, ensures a long-lasting machine and resistance to chemical aggression of the iron parts. Low-pressure wheels reduce the soil compression and the steering drawbar ensures easy handling. Combined with the fan units model HF or Antis with front suction, they guarantee an optimal coverage with a contemporary reduced power requirement also by high trunk-trees. The front cover and the lower guard keep the spraying control devices protected. Spraying control is realized through electrical systems, from simple electrical pressure adjustment to modern compatible ISOBUS solutions. Finally, NOBILI IOT BOX makes the sprayer compliant with Agriculture 4.0 benefits.









GEO HF 95-3000 litri
GEO HF 95-3000 litres



ANTIS V 92-3000 litri
ANTIS V 92-3000 litres



Caratteristiche tecniche - Technical Specifications

GEO	it.	rpm = 540 bar 0-50 litri/1'										 Potenza			
			Ø	Rpm	m/sec	mc/h			A mm	B mm	C mm	HP	KW	Kg	
90S-3000 T	3000	170/200	900	2.160	44	62.500	4-14	2-10	4515	1880	1650	70-80	51-59	1260	
HF 95-3000 T			950	1.775	40	75.200	4-16	2-12	4515	1880	1650	70-90	52-66	1230	
HF 110-3000 T			1100	1.775	44	95.730	6-18	2-14	4770	1880	1650	80-100	59-81	1325	
ANTIS															
92-3000T	3000	160/170	920	2.380	44	45.550	3-12	2-9	4515	1880	1650	70-80	51-59	1220	
92V-3000T			920	2.380	44	45.550	3-12	2-9	4515	1880	2305	70-80	51-59	1250	

Concessionario / Dealer

NOBILI



40062 MOLINELLA (Bologna) - Italy - Tel. +39 051 881444
www.nobili.com - info@nobili.com